



## ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Amber Glow / Rainbow Black
CUADRO	Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
HORQUILLA	Fox 38 Factory Live Valve, 170mm, FIT4 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Factory Live Valve, 205/60, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA DE SILLÍN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SILLÍN	Giant Romero SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM GX Eagle, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle
FRENOS	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]203mm
PALANCAS DE FRENOS	Shimano SLX BL-M7100
CASSETTE	SRAM XG-1275 Eagle, 10x52
CADENA	SRAM GX Eagle
JGO. PLATOS Y BIELAS	TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	SRAM DUB, press fit
RUEDAS	
LLANTAS	Giant TRX 2 29 WheelSystem
BUJES	Giant TRX 2 29 WheelSystem
RADIOS	Giant TRX 2 29 WheelSystem
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, EXO+, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

## CARACTERÍSTICAS

- Cuadro: Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
- Horquilla: Fox 38 Factory Live Valve, 170mm, FIT4 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
- Manetas de cambio: SRAM GX Eagle, 1x12
- Jgo. platos y bielas: TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
- Colores: Amber Glow / Rainbow Black

## GEOMETRÍA

CUADRO	S	M	L	XL
Longitud del tubo del sillín (mm)	431	431	464	496
Ángulo del tubo del sillín	76,4°	76,4°	76,4°	76,4°
Longitud del tubo superior (mm) (mm)	574	601	640	666
Longitud del tubo de dirección (mm) (mm)	100	100	110	120
Ángulo del tubo de dirección	64,6°	64,6°	64,6°	64,6°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	132,7	132,7	132,7	132,7
Distancia entre ejes (mm) (mm)	1191	1220	1262	1289
Longitud de la vaina (mm) (mm)	439	439	439	439
Caída de la caja de pedalier (mm) (mm)	27	27	27	27
Stack (mm) (mm)	622	622	631	640
Reach (mm) (mm)	423	451	488	511
Altura del suelo al tubo (mm) (mm)	757	759	781	804
Ancho del manillar (mm) (mm)	800	800	800	800
Longitud de la potencia (mm) (mm)	40	40	40	40
Longitud de las bielas (mm) (mm)	165	170	170	170
Tamaño de ruedas	29"	29"	29"	29"

*Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.*